

APPLICATION FOR A APPROACH  
HILLMAN TOWNSHIP

Date \_\_\_\_\_

Permit # \_\_\_\_\_

Fee Rec'd \_\_\_\_\_

Receipt # \_\_\_\_\_

By \_\_\_\_\_

Property owners name \_\_\_\_\_

Address of property owner \_\_\_\_\_

City \_\_\_\_\_ State \_\_\_\_\_ Zip code \_\_\_\_\_

Telephone # \_\_\_\_\_ Fax # \_\_\_\_\_

APPLICANT IF DIFFERENT THAN PROPERTY OWNER

NAME \_\_\_\_\_

Address \_\_\_\_\_

City \_\_\_\_\_ State \_\_\_\_\_ Zip code \_\_\_\_\_

Telephone # \_\_\_\_\_ Fax # \_\_\_\_\_

LEGAL  
DESCRIPTION \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

BRIEFLY DESCRIBE  
YOUR REQUEST \_\_\_\_\_

SIGNATURE OF APPLICANT \_\_\_\_\_

DATE \_\_\_\_\_

A person shall be required to construct or reconstruct an approach that meets these minimum specifications for the safety and for adequate drainage of the right-of-way. These specifications include, but are not necessarily limited to the following standards:

A. Culverts within approaches shall be a minimum of 12 inches in diameter and a minimum of 24 feet in length.

B. Approach culverts must be constructed of 16 gauge corrugated metal pipe. Any thing else would have to be approved by the Hillman Township Road Authority.

C. Approach in slope in the ditch at the culvert shall be no greater than 4:1 and shall be in compliance with Kanabec Co. entrance approach detail on attached page.

D. Only one driveway per roadway is permitted for each residential lot, unless approved by the Hillman Township Road Authority.

E. The minimum top width of a residential approach within the right-of-way shall be no less than 16 feet with a minimum of 6 inches of class five gravel on top.

F. All stumps, roots, logs, and brush shall be removed from the road bed that the culvert is to be installed.

Signature of Applicant \_\_\_\_\_

Date \_\_\_\_\_

Signature of Road Authority \_\_\_\_\_ Date \_\_\_\_\_